



Industrial bench scale model QAL/DCS series



Indicator Features:

- Real-time clock kit (date & time print)
- High A/D conversion technology; Conversion readability 1/40000
- Low power consumption, bright LED & Backlight LCD mode selectable
- Low Zero-tracking range, Zero range (manual/auto) setup
- Units: kg, lb, two customized units
- Zero range 0mV~8 mV
- Display 6 bits 1' LCD, 21 status indications
- Interface RS232C, selectable 1200/2400/4800/9600/19200 bps
- Power supply - 220VAC / 50/60Hz
- Built-in rechargeable battery 6V 1.3 AH(QA 6V4ah)
- High Accuracy – 60 000 divisions

Functions:

- ❖ Animal weighing
- ❖ Parts counting
- ❖ Weight checking
- ❖ Accumulating
- ❖ Weight hold
- ❖ Preset tare

Platform Features:

- Stainless steel platter
- Overload protection
- M12 adjustable feet
- Powder coated construction
- Removable Stainless steel column
- Height from platter to display - +/-35cm
- Platter dimensions - 30cm x 30cm & 30cm x 40cm
- Display can be tilt to eye-level

Printer options:

Receipt printer



Label printer



Model	Dimensions	Capacity	Accuracy
QAL-DCS3030	30cm x 30cm	0kg – 15kg	1g
QAL-DCS3040	30cm x 40cm	0kg - 60kg	2g