



# CZNEWTON IWE indicator

(General purpose and ideal for low visibility areas)

**LARGE RED LED DISPLAY - BEST OF THE BEST**

(QUALITY BY FAR SUPERIOR TO COMPETITORS...)

**CZNEWTON**



## Specifications

- ◆Accuracy: III
- ◆A/D conversion way:  $\Sigma$  -  $\Delta$  transformation way
- ◆A/D conversion rate: 30 times/SEC (optional)
- ◆Maximum number of A/D conversion: 20 bit
- ◆Input signal range: - 10 mV~ 15 mV
- ◆Input sensitivity:  $\geq 0.1\mu\text{V/d}$
- ◆Working temperature: - 10 ° C to 40 ° C
- ◆Dc power supply: built-in battery 6 V /4 AH (lead)
- ◆The ac power: - 240 V
- ◆Product size:  
220 mm (length) \* 180mm (wide) \* 85 mm (high)
- ◆Sensors for C5V bridge power.

RS232 output

## Standard Functions

- ◆High precision A/D conversion, readability 1/30000/60000;
- ◆With exact counting functions;  
Can realize manual cumulative function;
- ◆Power-off protection function in weight;  
With timing shutdown function;
- ◆Alternative and various backlight models;
- ◆Manual revision G value function all over the world;
- ◆With kg/T/G/lb/oz/viss/gangjin/taijin one key conversion function;
- ◆With multiple peaks, maintain stable value function;
- ◆With external calibration convenient functions;  
Achieve six sections of nonlinear correction.

## Features

- A built-in resistance to electromagnetic interference;
- ◆With undervoltage directives and protection device;
- ◆Special software technology, enhance the system's ability to resist vibration.