

## KW Weighing Indicator

### General Specifications

• Display	24mm digit LCD display, with white LED backlight
• Keyboard	7keys(Membrane keyboard)
• Housing	ABS plastic
• Max. Divisions	6,000e; 30,000d
• Load cell excitation voltage	5V/150mA
• ADC update	≤1/10 second
• Operate Temp	-10°C~+40°C
• Power	220VAC mains with rechargeable battery (6V/4Ah)
• Gross weight	2.5kg



- An economical general purpose instrument used in a variety of weighing application
- Selectable graduation sizes
- Application: 1. Check weighing 2. Simple parts counting 3. Accumulation 3. Auto print 4. Weighing units conversion
- OIML approval from Delta(approval no.:DK0199.165)
- Battery provide up to 70 hours of continuous use (without backlight)
- Optional RS-232 interface can connect LP-50 label printer, TPuP mini printer or computer






## KW Weighing Indicator

Model Name	Capacity	Readability	Division	Approx. weight	Approval
KW	X	X	30,000d	2.5kg	CE
KW-M	X	X	6,000e	2.5kg	CE, OIML

### Options

					
LP-50 Printer	TPuP Printer	OS-2130D Printer	A-2240 Printer	Alarm light	

### Dimensions(mm)



### Print formats

NO.: 1  
GS: 4.240KG

DATE: 2012/03/07  
TIME: 19:06:37  
NO.: 1  
GS: 4.235KG

DATE: 2012/03/07  
TIME: 19:08:26  
NO.: 2  
NT: 4.235KG  
TW: 1.810KG  
GW: 6.045KG

DATE: 2012/03/07  
TIME: 19:10:54  
TOTAL  
\*\*\*\*\*  
NO: 3  
Total: 12.705KG

DATE: 2012/03/07  
TIME: 19:09:03  
NO.: 1  
GS: 4.235KG  
TOTAL: 4.235KG

DATE: 2012/03/07  
TIME: 19:10:48  
NO.: 3  
NT: 4.235KG  
TW: 1.810KG  
GW: 6.045KG  
TOTAL: 12.705KG