



SHEKEL MERAV 2000DENISE Indicator series



SANS 1649 compliant- Legal for Trade

Versatility:

Connects to most receipt and label printers with print out information such as **suppliers name, date & time, consecutive no, weight and total weight**. An added controller board can be added for various character sizes and formats, etc.




General Specifications for various models:

- 6 digits 1" LCD Display
- All functions are programmable using 4 keys
- Flexible decimal point
- Division: 1, 2, 5, 10, 20, 100, 200, 500
- Accuracy: 3000d suits OIML-H44 standards
- Resolution: 10000d, 120000 internal divisions
- Analog / Digital Filter, analog signal with 3.3 μ V/sec sensitivity
- Tare or according to standard, including 'manual tare' option
- Connects up to 8 load cells 350ohm, p/supply 5V to each load cell
- Power source 50/60 Hz 230 VAC
- RS232 Communication to computer / printer
- Options:
 - Analog Communication BCD / 0-10V / 4-20mA
 - 4 set-points in the indicator or 8 in a separate box
 - Water & Dust Resistant - IP 67
 - Back light Display for dark areas
 - Live Stock Weighing Software
 - Peak-Hold software

MERAV 2000 O/P (Programmable Logic Control)

- Up to 8 x Load cells,
- Power: 220VAC mains only
- 4-20mA output, 0 - 10V, BCD
- RS232
- Weight memory



MERAV 2000 S/P (4 x set-point controller)

- Up to 8 x Load cells,
- Power: 220VAC mains
- Built-in 4 x set point minirel or external minirel with start/stop buttons.
- Weight memory