



SHEKEL MERAV 2000 O/P & S/P

Industrial Application Indicators

SABS Approved - Legal for Trade

❖ MERAV 2000 O/P (4-20mA)

❖ MERAV 2000 S/P (4 x set-point)



Standard specifications:

- 6 digits 1" LCD Display
- All functions are programmable using 4 keys
- Flexible decimal point
- Division: 1, 2, 5, 10, 20, 100, 200, 500
- Accuracy: 3000d suits OIML-H44 standards
- Resolution: 10000d, 120000 internal divisions
- Analog / Digital Filter, analog signal with 3.3µV/sec sensitivity
- Auto Tare and manual Tare input
- Connects up to 8 load cells 350ohm, p/supply 5V-10V to each load cell
- Power source 50/60 Hz 230 VAC
- RS232 Communication to PC or printer for model MERAV 2000 O/P only
- Weight memory
- **EASY PANEL MOUNT HOUSING**

Optional:

- Back light Display for dark areas



MERAV 2000 DENISE



Model/Specifications:

MERAV 2000 O/P (for PLC - Programmable Logic Control)

- Up to 8 x Load cells,
- Power: 220VAC mains only
- 4-20mA output, 0 - 10V, BCD, RS232 output
- Weight memory

MERAV 2000 S/P (for batching - 4 x set-point controller)

- Up to 8 x Load cells,
- Power: 220VAC mains
- Built-in 4 x set point controller or with external 8 x set-point minirel with start/stop button.
- Weight memory

Optional - Stainless steel housing

MERAV 2000 DENISE O/P or S/P (with 4-20mA or set-point)

- Fully stainless steel IP67 housing



PANEL MOUNT



Process control applications